

					
MEDITE, Redmondstown, Clonmel, Co. Tipperary, Ireland					
DOP09REV3 MEDITE TRICOYA EXTREME MDF.H					
EN 13986:2004+A1:2015					
Not Applicable					
04					
E1					
MDF.H					
External and internal use as non-structural components					
Thickness Range mm	4 to <9	9 to <12	12 to <15	15 to <18	18
Internal bond (N/mm²)	0.80	0.80	0.80	0.80	0.80
Swelling in thickness %	2.5	2.0	2.0	1.5	1.5
Internal bond after boil test (N/mm²)	0.65	0.65	0.65	0.65	0.65
Reaction to fire	NPD	E-s2,d0	E-s2,d0	E-s2,d0	E-s2,d0
Release of formaldehyde	E1	E1	E1	E1	E1
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm
Thermal resistance R Value m²k / W	0.056	0.085	0.114	0.150	0.180
Biological	Use Classes 1,2,3, 4				

CE symbol

Name and address of manufacturer
DoP reference.

Reference to harmonised standard

Notified body number

Year in which the CE mark was first affixed

Formaldehyde classification

Product technical class

Intended use

Thickness range

Declared performance