

DECLARATION OF PERFORMANCE

Reference number **DOP16REV5 MEDITE FR CLEAR MDF EUROCLASS B**

MEDITE
Redmondstown
Clonmel,
County Tipperary,
Ireland


Product type	Intended use	AVCP*	Notified Body reference
MDF	Internal use as non-structural components in dry conditions	1	Warrington Certification Limited 1121
*Assessment and verification of constancy of performance system according to Annex V of regulation (EU) No 305/2011			

Declared Performance

Essential characteristics	Performance		Harmonised technical specification
	6 to 9	>9 to 25	
Thickness Range (mm)	6 to 9	>9 to 25	EN 13986:2004+A1:2015
Internal bond (N/mm ²)	0.65	0.55	
Swelling in thickness (24hr) %	17	10	
Release of formaldehyde	E1	E1	
Reaction to fire	B-s2,d0	B-s2,d0	
Water vapour permeability μ	NPD	NPD	
Airborne sound insulation (surface mass) (R)	NPD	NPD	
Sound absorption Frequency range 250Hz to 500Hz (α)	NPD	NPD	
Sound absorption Frequency range 1000Hz to 2000Hz (α)	NPD	NPD	
Thermal conductivity	NPD	NPD	
Biological durability	Use Class 1		
Release (content) of pentachlorophenol (PCP)	≤5ppm		

The performance of the product identified is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Tom Prendergast, Technical Manager.

Clonmel, Ireland. 15/08/2019.