



## MEDITE EXTERIOR

Generated on 20.02.2020

### Detailed description

MDF panel developed specifically for use in a wide range of external applications and gives all the design freedom of interior MDF. Designed for use in external conditions in accordance with MDF.H (Option 2) as defined in BS EN 622-5.

### Applications:

- Substitute for softwood, hardwood, plastic and metal in external non-stressed applications.
- External signs, shop fronts and external woodwork (fascias, exterior mouldings).
- Garden furniture components, exterior display stands.

### Features:

- Suitable for use in external conditions.
- Suitable for use in Hazard Classes 1, 2 and 3 environments provided an appropriate coating system is used.
- MEDITE EXTERIOR is distinguishable from other MEDITE MDF products by its grey identification colour.
- Zero added formaldehyde during manufacture.

### Product guidance - As Standard

#### Fire rating:

Substrate is expected to achieve a fire class rating of Euro Class D.

#### Moisture content:

7% ± 2% at the time of manufacture.

### Options

#### Thickness:

Other thicknesses are available by special request.

### Product specification

#### Manufacturer

- Name: MEDITE SMARTPLY
- Web: [www.mdfofb.com](http://www.mdfofb.com)
- Email: [info@mdfofb.com](mailto:info@mdfofb.com)
- Tel: +44 (0)1322 424900

MEDITE SMARTPLY



#### MEDITE SMARTPLY

Persimmon House  
Anchor Boulevard  
Crossways Business Park  
Dartford  
Kent  
DA2 6QH

Tel: +44 (0)1322 424900

[www.mdfofb.com](http://www.mdfofb.com)  
[info@mdfofb.com](mailto:info@mdfofb.com)



- Fax: +44 (0)1322 424920

- Address: Persimmon House, Anchor Boulevard, Crossways  
Business Park, Dartford, Kent DA2 6QH

**Product reference** MEDITE EXTERIOR

**Size**  
1220 x 2440 mm  
1220 x 2745 mm  
1220 x 3050 mm  
1525 x 2745 mm

**Thickness**  
6 mm  
9 mm  
12 mm  
15 mm  
18 mm  
22 mm  
25 mm