



MEDITE TRICOYA EXTREME

Generated on 20.02.2020

Detailed description

MEDITE TRICOYA EXTREME (MTX) is characterized by its durability, dimensional stability and reliability properties achieved through the use of acetylated wood fibre in the manufacturing process. The resulting extreme moisture resistance ensures it excels in outdoor environments and does not crack or delaminate, remaining stable in all dimensions.

Independent testing by BRE shows an expected service life 60 years for exterior use.

Features:

- 50 year guarantee.
- Lower maintenance costs resulting from extended periods between exterior coating maintenance.
- Fungal resistant.
- Manufactured from FSC certified wood from sustainable sources.

Applications:

- Facade cladding, fascia and soffit panels.
- Window and door components, door skins.
- Wet interiors, including wall linings to swimming pools, wet rooms and changing rooms.
- Play frames, exterior composite furniture and buildings.

Product guidance - As Standard

Fire rating:

Substrate is expected to achieve a fire class rating of Euro Class E.

Moisture content:

Moisture content should be 10% before processing and coating applications.

Options

Thickness:

Other thicknesses are available by special request.

Product specification

Manufacturer

- Name: MEDITE SMARTPLY

MEDITE SMARTPLY



MEDITE SMARTPLY

Persimmon House
Anchor Boulevard
Crossways Business Park
Dartford
Kent
DA2 6QH

Tel: +44 (0)1322 424900

www.mdfofb.com
info@mdfofb.com



- Web: www.mdfosb.com
- Email: info@mdfosb.com
- Tel: +44 (0)1322 424900
- Fax: +44 (0)1322 424920
- Address: Persimmon House, Anchor Boulevard, Crossways
Business Park, Dartford, Kent DA2 6QH

Product reference	MEDITE TRICOYA EXTREME
Size	1220 x 2440 mm 1220 x 3050 mm - 15 or 18 mm thickness only.
Thickness	6 mm 9 mm 12 mm 15 mm 18 mm